

INDUSTRIAL COMPONENT DATA

FKIC 2,5 HC/ 4-ST-5,08 BD:9X2 1706909 PHOENIX CONTACT Plug-in part, rated current: 16 A, dimensioning voltag..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKIC 2,5 HC/ 4-ST-5,08 BD:9X2



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKIC 2,5 HC/ 4-ST-5,08 BD:9X2
Catalog number	1706909
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-FA2DB42850
Generated	2026-08-06

Product Overview

Plug-in part, rated current: 16 A, dimensioning voltage (III/2): 320 V, number of poles: 4, pitch: 5.08 mm, connection type: Push-in spring connection, color: green, contact surface: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 16 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Male, Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, number of connections: 4, family of articles: FKIC 2.5 HC/.. -ST, pitch: 5.08 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, Stecksystem: POWER COMBICON2.5, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Plug component, nominal current: 16 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5.08 mm, connection method: Push-in spring connection, color: green, contact surface: Tin

Your advantages

Time saving push-in connection, tools not requiredDefined contact force ensures that contact remains stable over the long termIntuitive use through colour coded actuation leverInverted connector with pin contacts for touch-proof device outputs or free-hanging cable/cable connectionsOptimized for tight installation situations: operation and conductor connection from one directionQuick and convenient testing using integrated test optionKey Commercial Data

Orderkey 1706909

Packing unit 1

GTIN 4046356889995

Custom tariff number 85366990

General

Range of articles FKIC 2,5 HC/..-ST

Type of contact Male connector

Number of positions 4

Connection method Push-in spring connection

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 16 A

Nominal cross section 2.5 mm²

Internal cylindrical gage A2

Stripping length 10 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conducto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKIC 2,5 HC/ 4-ST-5,08 BD:9X2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.