

INDUSTRIAL COMPONENT DATA

FL NAT 2208 2702882 PHOENIX CONTACT Managed NAT Switch 2000, 8 RJ45 ports 10/100 Mbps, degree of protection:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL NAT 2208



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL NAT 2208
Catalog number	2702882
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-F8A31A529D
Generated	2026-08-06

Product Overview

Managed NAT Switch 2000, 8 RJ45 ports 10/100 Mbps, degree of protection: IP20, PROFINET Conformance-Class B, 1:1-NAT, Virtual NAT, IP-Masquerading

Managed NAT Switch 2000, 8 RJ45 ports 10/100 MBit/s, PROFINET Conformance-Class B, 1:1-NAT, Virtual NAT, IP-Masquerading

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2702882

Packing unit 1 pc

Catalog page Page 328 (C-6-2019)

GTIN 4055626384825

Weight per Piece (excluding packing) 400.000 g

Custom tariff number 85176200

Country of origin DE (Germany)

Note

Ambient conditions

Function

Supply voltage

Connection data

Environmental Product Compliance

Dimensions

Interfaces

Network expansion parameters

General

Standards and Regulations

Classifications

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

[Back to top](#)Dimensions

Width 45 mm

Height 130 mm

Depth 115 mm

[Back to top](#)Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating)

Air pressure (storage/transport) 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating)

[Back to top](#)Interfaces

Interface Ethernet (RJ45)

No. of ports 8 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Copper

Transmission speed 10/100 Mbps

Transmission length 100 m (per segment)

Signal LEDs Data receive, link status

[Back to top](#)Function

Basic functions Store-and-forward switch, complies with IEEE 802.3

Management Web-based management (HTTP/HTTPS)

SNMPv1/v2/v3....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL NAT 2208 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.