

INDUSTRIAL COMPONENT DATA

FL NAT 2304-2GC-2SFP 2702981 PHOENIX CONTACT

Managed NAT Switch 2000, 4 RJ45 ports 10/100/1000 Mbps, 2 SFP p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL NAT 2304-2GC-2SFP



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL NAT 2304-2GC-2SFP
Catalog number	2702981
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-5E5F023EBE
Generated	2026-08-06

Product Overview

Managed NAT Switch 2000, 4 RJ45 ports 10/100/1000 Mbps, 2 SFP ports 100/1000 Mbps, 2 Combo ports 10/100/1000 Mbps, degree of protection: IP20, PROFINET Conformance-Class B, 1:1-NAT, Virtual NAT, IP-Masquerading
Managed NAT Switch 2000, 4 RJ45 ports 10/100/1000 MBit/s, 2 SFP ports 100/1000 MBit/s, 2 Combo ports 10/100/1000 MBit/s, PROFINET Conformance-Class B, 1:1-NAT, Virtual NAT, IP-Masquerading

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data
Orderkey 2702981
Packing unit 1 pc
Catalog page Page 328 (C-6-2019)
GTIN 4055626446035
Weight per Piece (excluding packing) 460.000 g
Custom tariff number 85176200
Country of origin DE (Germany)
Dimensions
Interfaces

Network expansion parameters

General

Standards and Regulations

Classifications

Ambient conditions

Function

Supply voltage

Connection data

Environmental Product Compliance

Dimensions

Width 45 mm

Height 130 mm

Depth 115 mm

Back to topAmbient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating)

Air pressure (storage/transport) 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating)

Back to topInterfaces

Interface Ethernet (RJ45)

No. of ports 4 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Copper

Transmission speed 10/100/1000 Mbps

Transmission length 100 m (per segment)

Signal LEDs Data receive, link status

Interface SFP module

No. of ports 2 (SFP ports)

Transmission physics Depending on the SFP module

Transmission speed 100/1000 Mbps (full duplex)

Transmission length up to 80 km (Depending on the fiber/SFP module used)

Signal LEDs Data receive, link status

Inte...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL NAT 2304-2GC-2SFP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.