

INDUSTRIAL COMPONENT DATA

FL SWITCH 1005N 1085039 PHOENIX CONTACT Narrow Ethernet switch, five RJ45 ports with 10/100 Mbit/s on all po..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 1005N



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 1005N
Catalog number	1085039
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-DECE407441
Generated	2026-08-05

Product Overview

Narrow Ethernet switch, five RJ45 ports with 10/100 Mbit/s on all ports, automatic transmission rate detection, autocrossing function and QoS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 1085039

Packing unit 1 pc

Weight per Piece (excluding packing) 220.000 g

Country of origin TW (Taiwan)

Note

Ambient conditions

Function

Supply voltage

Connection data

Classifications

Dimensions

Interfaces

Network expansion parameters

General**Standards and Regulations****Note**

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Back to top**Dimensions**

Width 22.5 mm

Height 117 mm

Depth 84 mm

Note on dimensions 123 mm with connector

Back to top**Ambient conditions**

Degree of protection IP30

Ambient temperature (operation) -10 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating)

Air pressure (storage/transport) 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating)

Back to top**Interfaces**

Interface Ethernet (RJ45)

No. of ports 5 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Ethernet in RJ45 twisted pair

Transmission speed 10/100 Mbps

Transmission length 100 m (per segment)

Signal LEDs Data receive, link status

Back to top**Function**

Basic functions Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode

Additional functions Autonegotiation

MAC address table 2k

PROFINET...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 1005N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.