

INDUSTRIAL COMPONENT DATA

FL SWITCH 1016N 1085255 PHOENIX CONTACT Narrow Ethernet switch, sixteen RJ45 ports with 10/100 Mbit/s on all..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 1016N



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 1016N
Catalog number	1085255
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-22BE4030C0
Generated	2026-08-06

Product Overview

Narrow Ethernet switch, sixteen RJ45 ports with 10/100 Mbit/s on all ports, automatic transmission rate detection, autocrossing function and QoS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 1085255

Packing unit 1 pc

Weight per Piece (excluding packing) 360.000 g

Country of origin TW (Taiwan)

Note

Ambient conditions

Function

Supply voltage

Connection data

Classifications

Dimensions

Interfaces

Network expansion parameters

General**Standards and Regulations****Note**

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Back to topDimensions

Width 40 mm

Height 140.4 mm

Depth 92 mm

Note on dimensions 150 mm with connector

Back to topAmbient conditions

Degree of protection IP30

Ambient temperature (operation) -10 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating)

Air pressure (storage/transport) 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating)

Back to topInterfaces

Interface Ethernet (RJ45)

No. of ports 16 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Ethernet in RJ45 twisted pair

Transmission speed 10/100 Mbps

Transmission length 100 m (per segment)

Signal LEDs Data receive, link status

Back to topFunction

Basic functions Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode

Additional functions Autonegotiation

MAC address table 8k

PROFINE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 1016N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.