

INDUSTRIAL COMPONENT DATA

FL SWITCH 1105NT-2SFP 1343025 PHOENIX CONTACT

Narrow Ethernet switch, wide temperature range, five RJ45 port..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 1105NT-2SFP



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 1105NT-2SFP
Catalog number	1343025
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-7B43D3C328
Generated	2026-08-04

Product Overview

Narrow Ethernet switch, wide temperature range, five RJ45 ports with 10/100/1000 MBit/s on all ports, automatic transmission rate detection, Autocrossing function and QoS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Technical dataDimensionsWidth 22.5 mm

Height 148 mm

Depth 98 mm

NotesUtilization restriction

EMC note EMC: class A product, see manufacturer's declaration in the download area

Material specificationsHousing material Polycarbonate fiber reinforced

Aluminum / steel sheet DC01

MountingMounting type DIN rail mounting

InterfacesEthernet (RJ45)

Number of interfaces 5

Connection method RJ45

Note on the connection method Auto negotiation and autocrossing

Transmission speed 10/100/1000 Mbps
Transmission physics Ethernet in RJ45 twisted pair
Transmission length 100 m (per segment)
Signal LEDs Data receive, link status
No. of channels 5 (RJ45 ports)
Ethernet (SFP)
Number of interfaces 2
Connection method SFP
Transmission speed 100/1000 Mbps (full duplex)
Transmission physics Depending on the SFP module
Transmission length up to 40 km (Depending on the fiber/SFP module used)
Signal LEDs Data receive, link status
No. of channels 2 (SFP ports)
Product properties Product type Switch
Product family Unmanaged Switch 1000
MTTF 75.5 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)
1013.7 Years (SN 29500 standard, temperature 25°C, operating cycle 21%)
776.4 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day))
Switch functions
Basic functions Unmanaged switch
Autonegotiation
Store and Forward switching mode
MAC address table 4k
Status and diagnostic indicators LEDs: US, link and activity per port
Additional functions 100 BASE-TX/1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 1105NT-2SFP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.