

INDUSTRIAL COMPONENT DATA

FL SWITCH 2206-2FX ST 2702332 PHOENIX CONTACT

Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 2206-2FX ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 2206-2FX ST
Catalog number	2702332
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-87627A1486
Generated	2026-08-04

Product Overview

Industrial Ethernet Switch
Managed Switch 2000, 6 RJ45 ports 10/100 MBit/s, 2 Multimode ST 100 MBit/s, PROFINET Conformance-Class B, Extended temperature range

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2702332
Packing unit 1 pc
Catalog page Page 405 (C-6-2017)
GTIN 4055626128597
Weight per Piece (excluding packing) 420.700 g
Custom tariff number 85176200
Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 45 mm
Height 130 mm

Depth 115 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 68 kPa ... 108 kPa (3000 m above sea level)

Air pressure (storage/transport) 68 kPa ... 108 kPa (3000 m above sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 6 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Copper

Transmission speed 10/100 Mbps

Transmission length 100 m (per segment)

Signal LEDs Data receive, link status

Interface 2 Ethernet FO

No. of ports 2 (ST multi-mode)

Transmission physics multi-mode fiberglass

Transmission speed 100 Mbps (full duplex)

Transmission length 11000 m (fiberglass with F-G 62.5/125 0.7 dB/km F1000)

6400 m (fiberglass with F-G 50/125 0.7 dB/km F1200)

3000 m (fiberglass with F-G 62.5/125 2.6 dB/km F600)

2800 m (fiberglass with F-G 50/125 1.6 dB/km F800)

Wavelength 1300 nm

Signal LEDs Data receive, link status

Fu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 2206-2FX ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.