

INDUSTRIAL COMPONENT DATA

FL SWITCH 2214-2SFX PN 1044030 PHOENIX CONTACT

Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 2214-2SFX PN



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 2214-2SFX PN
Catalog number	1044030
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-22560BF97F
Generated	2026-08-03

Product Overview

Industrial Ethernet Switch

Managed Switch 2000, 14 RJ45 10/100 MBit/s ports, 2 SFP 100 MBit/s ports, PROFINET Conformance-Class B, Extended temperature range, Preset PROFINET mode, PROFINET status LEDs

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 1044030

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626611792

Weight per Piece (excluding packing) 470.000 g

Custom tariff number 85176200

Country of origin DE (Germany)

Dimensions

Width 85 mm

Height 130 mm

Depth 115 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 68 kPa ... 108 kPa (3000 m above sea level)

Air pressure (storage/transport) 68 kPa ... 108 kPa (3000 m above sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 14 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Copper

Transmission speed 10/100 Mbps

Transmission length 100 m (per segment)

Signal LEDs Data receive, link status

Interface 2 SFP module

No. of ports 2 (SFP ports)

Transmission physics Depending on the SFP module

Transmission speed 100 Mbps (full duplex)

Transmission length up to 40 km (Depending on the fiber/SFP module used)

Signal LEDs Data receive, link status

Function

Basic functions Store-and-forward switch, complies with IEEE 802.3

Management Web-based management (HTTP/HTTPS)

SNMPv1/v2/v3

Command-line interface (Telnet, SSH)

Diagnostic functions RMON History

LLDP (Link Layer Discovery Protocol)

SNMP-Traps

N:1-Portmirroring

ACD (A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 2214-2SFX PN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.