

**INDUSTRIAL COMPONENT DATA**

# FL SWITCH 2304-2GC-2SFP 2702653 PHOENIX CONTACT

## Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 2304-2GC-2SFP



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | PHOENIX CONTACT         |
| MPN / Reference | FL SWITCH 2304-2GC-2SFP |
| Catalog number  | 2702653                 |
| Category        | Network switch          |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-A8379D10B6           |
| Generated       | 2026-08-04              |

### Product Overview

Industrial Ethernet Switch

Managed Switch 2000, 4 RJ45 ports 10/100/1000 MBit/s, 2 SFP ports 100/1000 MBit/s, 2 Combo ports 10/100/1000 MBit/s, PROFINET Conformance-Class B, Extended temperature range

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                       |
|--------------|-----------------------|
| Catalog path | PHOENIX CONTACT > I/O |
|--------------|-----------------------|

### Additional Product Information

Key Commercial Data

Orderkey 2702653

Packing unit 1 pc

Catalog page Page 407 (C-6-2017)

GTIN 4055626259994

Weight per Piece (excluding packing) 451.100 g

Custom tariff number 85176200

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 45 mm

Height 130 mm

Depth 115 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 53 kPa ... 108 kPa (5000 m above sea level)

Air pressure (storage/transport) 53 kPa ... 108 kPa (5000 m above sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 4 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Copper

Transmission speed 10/100/1000 Mbps

Transmission length 100 m (per segment)

Signal LEDs Data receive, link status

Interface 2 SFP module

No. of ports 2 (SFP ports)

Transmission physics Depending on the SFP module

Transmission speed 100/1000 Mbps (full duplex)

Transmission length up to 80 km (Depending on the fiber/SFP module used)

Signal LEDs Data receive, link status

Interface 3 Ethernet (combo)

No. of ports 2 (Combo ports)

Connection method SFP or RJ45 ports

Note on the connection method Auto negotiation and autocrossing

Transmissi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 2304-2GC-2SFP with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.