

INDUSTRIAL COMPONENT DATA

FL SWITCH 2314-2SFP PN 1031683 PHOENIX CONTACT

Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 2314-2SFP PN



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 2314-2SFP PN
Catalog number	1031683
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-2476F7693D
Generated	2026-08-03

Product Overview

Industrial Ethernet Switch

Managed Switch 2000, 14 RJ45 ports 10/100/1000 MBit/s, 2 SFP ports 100/1000 MBit/s, PROFINET Conformance-Class B, Extended temperature range, Preset PROFINET mode, PROFINET status LEDs

Managed Switch 2000, 14 RJ45 ports 10/100/1000 MBit/s, 2 SFP ports 100/1000 MBit/s, PROFINET Conformance-Class B, Extended temperature range, Preset PROFINET mode, PROFINET status LEDs, Development process certified according to IEC 62443-4-1, Compatible with IEC 62443-4-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 1031683

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626535289

Weight per Piece (excluding packing) 470.000 g

Custom tariff number 85176200

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 85 mm

Height 130 mm

Depth 115 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 53 kPa ... 108 kPa (5000 m above sea level)

Air pressure (storage/transport) 53 kPa ... 108 kPa (5000 m above sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 14 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Copper

Transmission speed 10/100/1000 Mbps

Transmission length 100 m (per segment)

Signal LEDs Data receive, link status

Interface 2 SFP module

No. of ports 2 (SFP ports)

Transmission physics Depending on the SFP module

Transmission speed 100/1000 Mbps (full duplex)

Transmission length up to 80 km (Depending on the fiber/SFP module used)

Signal LEDs Data receive, link status

Function

Basic functions Store-and-forward switch, complies with IEEE 802.3

Management Web-based management (HTTP/HTTPS)

SNMPv1/v2/v3

Command-line interface (Telnet...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 2314-2SFP PN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.