

**INDUSTRIAL COMPONENT DATA**

# FL SWITCH 4000T-8POE-2SFP 1026923 PHOENIX CONTACT

## Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 4000T-8POE-2SFP



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | PHOENIX CONTACT           |
| MPN / Reference | FL SWITCH 4000T-8POE-2SFP |
| Catalog number  | 1026923                   |
| Category        | Network switch            |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-DB45A1F943             |
| Generated       | 2026-08-04                |

### Product Overview

Industrial Ethernet Switch

Managed PoE Switches 4000, 2 SFP Ports 100/1000 MBit/s, 8 RJ45 Ports 10/100 MBit/s

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; I/O

### Additional Product Information

Key Commercial Data

Orderkey 1026923

Packing unit 1 pc

GTIN 4055626519555

Weight per Piece (excluding packing) 1,612.000 g

Custom tariff number 85176200

Country of origin TW (Taiwan)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 75 mm

Height 170 mm

Depth 152 mm

Ambient conditions

Degree of protection IP30

Ambient temperature (operation) -40 °C ... 75 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Air pressure (storage/transport) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)

Interfaces

Interface 2 Fiber optic interface

No. of ports 2 (SFP ports)

Transmission physics Depending on the SFP module

Transmission speed 100/1000 Mbps (full duplex)

Transmission length up to 80 km (Depending on the fiber/SFP module used)

Interface 3 Ethernet (PoE)

No. of ports 8 (RJ45 ports)

Connection method RJ45

Note on the connection method Auto negotiation and autocrossing

Transmission physics Ethernet in RJ45 twisted pair

Transmission speed 10/100 Mbps

Transmission length 100 m

Function

Basic functions Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP,....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 4000T-8POE-2SFP with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.