

INDUSTRIAL COMPONENT DATA

DF-UPBV 2,5/ 4 3060432 PHOENIX CONTACT Flange cover

Brand: PHOENIX CONTACT | Manufacturer Part Number: DF-UPBV 2,5/ 4



Manufacturer	PHOENIX CONTACT
MPN / Reference	DF-UPBV 2,5/ 4
Catalog number	3060432
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-CDE048D9E7
Generated	2026-08-03

Product Overview

Flange cover

Covers with fastening flange, snap-on to the UPBV 2.5/... and UPBV 4/..., connection type: Screw connection, length: 45.7 mm, width: 4.5 mm, height: 32 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3060432

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 370 (C-1-2017)

GTIN 4046356147033

Weight per Piece (excluding packing) 2.060 g

Custom tariff number 85389099

Country of origin DE (Germany)

General

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Dimensions

Width 4.5 mm

Length 45.7 mm

Height 32 mm

Connection data

Connection method Screw connection

Screw thread M2,5

Tightening torque, min 0.4 Nm

Tightening torque max 0.5 Nm

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for rail ve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DF-UPBV 2,5/ 4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.