

INDUSTRIAL COMPONENT DATA

DFS-CP 2,5-4L 3012321 PHOENIX CONTACT Flange cover

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFS-CP 2,5-4L



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFS-CP 2,5-4L
Catalog number	3012321
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-D26B5BA220
Generated	2026-08-04

Product Overview

Flange cover

Clamping flange caps, length: 31.6 mm, width: 5.2 mm, height: 26 mm, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3012321

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 290 (C-1-2017)

GTIN 4046356661850

Weight per Piece (excluding packing) 0.910 g

Custom tariff number 85389099

Country of origin PL (Poland)

General

Color gray

Material PA

Flammability rating according to UL 94 V0

Dimensions

Width 5.2 mm

Length 31.6 mm

Height 26 mm

General

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFS-CP 2,5-4L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.