

INDUSTRIAL COMPONENT DATA

C-SCM 2,5/6,3X0,8 3240162 PHOENIX CONTACT Connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: C-SCM 2,5/6,3X0,8



Manufacturer	PHOENIX CONTACT
MPN / Reference	C-SCM 2,5/6,3X0,8
Catalog number	3240162
Category	Crimp splices for copper conductor
Minimum order	100 Pcs
Document ID	EO-E92A65748F
Generated	2026-08-03

Product Overview

Connector

Flat, uninsulated connector, 1.5 - 2.5 mm², 6.3 x 0.8Flat connector, non-insulated, 1.5 - 2.5 mm², 6.3 x 0.8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > TOOL fox

Additional Product Information

Technical dataProduct propertiesProduct type Connector

Data management status

Article revision 00

Electrical propertiesFuse DIN 46248

DimensionsDimensional drawing

Width 6.3 mm

Sleeve length 20 mm

Maximum stripping length 8 mm

Min. material thickness 0.8 mm

Material specificationsColor silver-colored

Material Brass

Coating tin-plated

Insulating material nicht zutreffend

Mechanical propertiesTechnical data

Sleeve length 20 mm

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) 110 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-SCM 2,5/6,3X0,8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.