

## INDUSTRIAL COMPONENT DATA

# C-BCSI 1,5/9X2,8 3240531 PHOENIX CONTACT Cable lug

Brand: PHOENIX CONTACT | Manufacturer Part Number: C-BCSI 1,5/9X2,8



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | C-BCSI 1,5/9X2,8                                  |
| Catalog number  | 3240531                                           |
| Category        | Solderless copper terminals for copper conductors |
| Minimum order   | 100 Pcs                                           |
| Document ID     | EO-70C043E28F                                     |
| Generated       | 2026-08-03                                        |

## Product Overview

Cable lug

Flat male terminal, red, 0.5 - 1.5 mm<sup>2</sup>, male dimension 20x2.8mmFlat pin cable lug, red, 0.5 - 1.5 mm<sup>2</sup>, pin dimensions: 20 x 2.8 mm

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                            |
|--------------|----------------------------|
| Catalog path | PHOENIX CONTACT > TOOL fox |
|--------------|----------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Connector

Data management status

Article revision 00

Electrical propertiesFuse no

DimensionsDimensional drawing

Width 2.8 mm

Sleeve length 19.5 mm

Length of the insulating material sleeve 10.5 mm

Length contact range 9 mm

Maximum stripping length 7 mm

Min. material thickness 0.75 mm

Inner dimensions of the insulating collar 4.1 mm

Material specificationsColor red (RAL 3001)

Material Cu

Flammability rating according to UL 94 V2

Coating electrogalvanized

Insulating material PA

Components halogen-free

Mechanical properties Technical data

Sleeve length 19.5 mm

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -20 °C ... 105 °C

Permanent temperature 105 °C

Short-term temperature 120 °C

ETIM for 3240531 Cable terminations and insulation products (EC001052)

Feature Name

Feature Value

Nominal cross section (EF005124)

0.5 mm<sup>2</sup>

Material (EF002169)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-BCSI 1,5/9X2,8 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.