


INDUSTRIAL COMPONENT DATA

UK 6-FSI/C 3118203 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 6-FSI/C



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 6-FSI/C
Catalog number	3118203
Category	Fuse terminal block
Minimum order	1 Pcs
Document ID	EO-BC42EF255D
Generated	2026-08-01

Product Overview

Fuse modular terminal block

Fuse rail terminal, fuse type: Flat, fuse type: C, nominal voltage: 250 V, nominal current: 30 A, number of poles: 1, connection type: Screw connection, 1st floor, Dimensioning section: 4 mm², section: 0.2 mm²- 10 mm², mounting class: NS 35/7.5, NS35/15, NS32, color: black

Fuse modular terminal block, fuse type: Flat, fuse type: C, nom. voltage: 250 V, nominal current: 30 A, number of positions: 1, connection method: Screw connection, 1 level, Rated cross section: 4 mm², cross section: 0.2 mm²- 10 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesGeneral

Note The current is determined by the fuse used, the voltage by the fuse or selected light indicator.

Product propertiesProduct type Fuse terminal block

Number of positions 1

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 17

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Fuse type Flat

Rated surge voltage 4 kV

Maximum power dissipation for nominal condition 1.31 W

Fuse C

Maximum current with single arrangement 30 A (special arrangements on request)

Connection data Number of connections per level 2

Nominal cross section 6 mm²

1 level

Screw thread M4

Tightening torque 1.5 ... 1.6 Nm

Stripping length 10 mm

Internal cylindrical gage A5

Connection in acc. with standard IEC 60947-7-3

Conductor cross section rigid 0.2 mm² ... 10 mm²

Cross section AWG 24 ... 8 (converted acc. to IEC)

Conductor cross section flexible 0.2 mm² ... 6 mm²

Conductor cross section, flexible [AWG] 24 ... 10 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 6 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²

2 conductors with same cross section, solid 0.2 mm² ... 2.5 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 2.5 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with the same cross section, flexible, with TWIN f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 6-FSI/C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.