

## INDUSTRIAL COMPONENT DATA

# UK 6-FSI/C-LED12 3001925 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 6-FSI/C-LED12



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | UK 6-FSI/C-LED12    |
| Catalog number  | 3001925             |
| Category        | Fuse terminal block |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-379B46F3CA       |
| Generated       | 2026-08-01          |

## Product Overview

Fuse modular terminal block

Terminal block for flat fuse, cross-section: 0.2-6 mm<sup>2</sup>, AWG: 26-8, width: 8.2 mm, colour: Black, with light indication, light indicator voltage: 12 V DC, light indicator current: 2 mA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3001925

Packing unit 50 pc

Catalog page Page 461 (C-1-2017)

GTIN 4017918100964

Weight per Piece (excluding packing) 21.120 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Mounting type NS 35/7,5

Color black

Number of positions 1  
Insulating material PA  
Flammability rating according to UL 94 V0  
Electrical data  
Fuse C  
Fuse type Flat  
Degree of pollution 3  
Insulating material group I  
Connection in acc. with standard IEC 60947-7-3  
Maximum current with single arrangement 30 A (special arrangements on request)  
Voltage LED 12 V DC (LED red)  
Current LED 2 mA DC (LED red)  
Dimensions  
Width 8.2 mm  
Height NS 35/7,5 52 mm  
Height NS 35/15 59.5 mm  
Height NS 32 57 mm  
Connection data  
Conductor cross section solid min. 0.2 mm<sup>2</sup>  
Conductor cross section solid max. 10 mm<sup>2</sup>  
Conductor cross section flexible min. 0.2 mm<sup>2</sup>  
Conductor cross section flexible max. 6 mm<sup>2</sup>  
Conductor cross section AWG min. 24  
Conductor cross section AWG max. 8  
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm<sup>2</sup>  
2 conductors with same cross section, solid min. 0.2 mm<sup>2</sup>  
2 conductors with same cross section, solid max. 2.5 mm<sup>2</sup>  
2 conductors with same cross section, stranded....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 6-FSI/C-LED12 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.