

INDUSTRIAL COMPONENT DATA

FLK 50-PA/EZ-DR/KS/ 300/YOC 2314406 PHOENIX CONTACT

Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLK 50-PA/EZ-DR/KS/ 300/YOC



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLK 50-PA/EZ-DR/KS/ 300/YOC
Catalog number	2314406
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-1DF22F81AB
Generated	2026-08-06

Product Overview

Front adapters

Front cast iron adapter with fixed round cable and a 50-pole plug pin extruded on both sides for the connection of Yokogawa ProSafe control systems. Cable length: 3.0 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2314406

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 190 (IF-2007)

GTIN 4046356100359

Weight per Piece (excluding packing) 674.100 g

Custom tariff number 85444290

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -20 °C ... 55 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. permissible operating voltage 30 V DC
Max. permissible current 500 mA (per path at 55°C)
Connection data 1
Connection name Controller level
Connection method Yokogawa, I/O cards compatible
Torque 0.5 Nm (Screw connection)
Number of connections 1
Number of positions 50
Connection data 2
Connection name Field level
Connection method Yokogawa, KS compatible
Torque 0.5 Nm (Screw connection)
Number of connections 1
Number of positions 50
Cable
Structural data in acc. to UL style 2464/1061
Conductor construction: Number of litz wires: 7
Single wire, material Cu tin-plated
Single wire, cross section 0.14 mm²
External diameter 11 mm
Length of cable 3 m
Outer sheath, material PVC
External sheath, color gray RAL 7035
Shielding yes
Halogen-free cable No
Max. conductor resistance 0.16 Ω /m
Cable insulation resistance approx. 153 M Ω /km
Cable impedance approx. 120 Ω
Cable resistance approx. 155 Ω /km
Cable capacity approx. 130 pF/m
Insulation Semi-rigid PVC
Supported controller
Controller Yokogawa ProSafe-RS
- suitable I/O card
Standards and Regulations
Flame resistance IEC 60332-3-22
Resistance to oil DIN VDE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLK 50-PA/EZ-DR/KS/ 300/YOC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.