

INDUSTRIAL COMPONENT DATA

FLKM 14/8P/HF/PLC 2295680 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 14/8P/HF/PLC



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 14/8P/HF/PLC
Catalog number	2295680
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-35E899AEE3
Generated	2026-08-02

Product Overview

Interface module

VARIOFACE interconnect module, for 8 channels with an additional terminal block for each signal, for a common positive potential, halogen-free

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2295680

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4017918429638

Weight per Piece (excluding packing) 124.450 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 56.3 mm

Height 77 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

General

Max. perm. operating voltage 60 V AC/DC

Max. perm. current (per branch) 1 A

Max. permissible current (all branches) 3 A (for plus and minus)

Mounting position any

Degree of protection IP00

Connection data for connection 1

Connection name Control side

Connection in acc. with standard IEC 60603-13

Connection method FLK14 pin strip

Number of positions 14

Connection data for connection 2

Connection name Field level

Connection method Screw connection

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Number of positions 20

Standards and Regulations

Designation Air clearances and creepage distances

Standards/regulations DIN EN 50178: 1998-04

Rated insulation voltage 63 V

Rated surge voltage 0.6 kV (1.2/50 us)

Insulation Functional insulation

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 14/8P/HF/PLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.