

**INDUSTRIAL COMPONENT DATA**

# FLKM-2KS50/PMT/ADV151/YCS 2321884 PHOENIX CONTACT

## Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-2KS50/PMT/ADV151/YCS



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | PHOENIX CONTACT           |
| MPN / Reference | FLKM-2KS50/PMT/ADV151/YCS |
| Catalog number  | 2321884                   |
| Category        | Interface module          |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-9441460ED2             |
| Generated       | 2026-08-05                |

### Product Overview

Passive module

VARIOFACE input module with screw connection, 32 channels, redundant connection connector for Yokogawa ADV151, ADV161 input cards.

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; INTERFACE Components (IF)

### Additional Product Information

Key Commercial Data

Orderkey 2321884

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356563703

Weight per Piece (excluding packing) 643.000 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 232 mm

Height 111 mm

Depth 68 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 70 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

#### General

Note Voltage monitoring on the module does not work in combination with upstream HESILED fuse terminal blocks with integrated LED display.

Max. perm. operating voltage 24 V DC

Max. perm. current (per branch) 63 mA AC (protected by fuse, observe derating)

Max. permissible current (all branches) 2 A (protected by fuse, observe derating)

Mounting position any

Assembly instructions In rows with zero spacing

Degree of protection IP00

Connection data for connection 1

Connection name Field level

Connection method Screw connection

Conductor cross section solid 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Conductor cross section AWG 24 ... 12

Number of connections 1

Number of positions 64

Connection data for connection 2

Connection name Controller level

Connection method Yokogawa KS-compatible

Torque 0.5 Nm

Number of connections 2

Number of positions 50

Note Usable system cables: Phoenix Contact YUC50, Yokogawa AKB331

#### Standards and Regulations

Designation Air clearances and creepage distances between the power circuits

Standards/regulations DIN EN 50178

Rated insul...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-2KS50/PMT/ADV151/YCS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.