


INDUSTRIAL COMPONENT DATA

FLKM 50/32M/OUT/LA/DV 2304843 PHOENIX CONTACT

Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 50/32M/OUT/LA/DV



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 50/32M/OUT/LA/DV
Catalog number	2304843
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-F890CCEDA2
Generated	2026-08-06

Product Overview

Passive module

32-channel module with LED and 2-conductor connection; common negative potential (for Delta V control system output cards)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2304843

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 285 (NTK-2006)

GTIN 4017918981754

Weight per Piece (excluding packing) 311.480 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 169 mm

Height 90 mm

Depth 68 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 30 V DC

Max. perm. current (per branch) 10 mA (IN: LED in series)

Max. permissible current (separate power supply) 5 A (KL/KL)

Number of positions 50

Status display Yes

Mounting position any

Assembly instructions In rows with zero spacing

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 50

Pitch 2.54 mm

Supported controller

Controller Emerson DeltaV

- suitable I/O card VE4002S1T2B6

Standards and Regulations

Standards/regulations IEC 60664

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "D..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 50/32M/OUT/LA/DV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.