


INDUSTRIAL COMPONENT DATA

FLKM 50/LA/PLC 2284552 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 50/LA/PLC



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 50/LA/PLC
Catalog number	2284552
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-635F9B6F2C
Generated	2026-07-31

Product Overview

Passive module

VARIOFACE interconnect module, with light indication, for 32 channels

VARIOFACE interface module, with LED, for 32 channels

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Interface module

Product family VARIOFACE

Number of positions 50

No. of channels 32

Data management status

Article revision 11

Insulation characteristics: Air clearances and creepage distances

Insulation Functional insulation

Overvoltage category II

Pollution degree 2

Electrical propertiesOperating voltage range 19.2 V DC ... 26.4 V DC

Current (per branch) <= 1 A

Current (Voltage supply per byte) <= 2 A

Air clearances and creepage distances
Rated insulation voltage 63 V
Rated surge voltage 0.6 kV (1.2/50 us)
Supported controller SIEMENS S7-400
Suitable I/O card 6ES7421-1BL01-0AA0
6ES7422-1BL00-0AA0
6ES7422-7BL00-0AB0
Supported controller ALLEN-BRADLEY ControlLogix
Suitable I/O card 1756-IB32
1756-OB32
Supported controller ALLEN-BRADLEY PLC 5
Suitable I/O card 1771 IBN
1771 OBN
Supported controller HONEYWELL Experion PKS C200
Suitable I/O card TC-IDD 321
TC-ODD 321
Supported controller MITSUBISHI MELSEC Q
Suitable I/O card QX81
QY81P
Supported controller SCHNEIDER ELECTRIC Modicon TSX QUANTUM
Suitable I/O card DDI 353
DDI 853
DDO 353
Supported controller SIEMENS S7-300 / ET 200 M
Suitable I/O card CPU 313C-2DP
CPU 314C-2DP
CPU 314C-2PtP
6ES7321-1BL00-0AA0
6ES7322-1BL00-0AA0
6ES7323-1BL00-0AA0
CPU 313C
CPU 313C-2PtP
Connection dataConnection 1 (control level)
Connection in acc. with standard IEC 60603-13
Connection method IDC/FLK pin strip
Number of connections 1
Number of positions 50
Insertion/withdrawal cycles > 50
Pitch 2.54 mm
Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 50/LA/PLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.