


INDUSTRIAL COMPONENT DATA

FLKM-M12/M/8P/2A/SC043 2903739 PHOENIX CONTACT

Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-M12/M/8P/2A/SC043



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-M12/M/8P/2A/SC043
Catalog number	2903739
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-C8FB57D445
Generated	2026-08-02

Product Overview

Interface module

VARIOFACE module, with spring-loaded terminals and M12-SAC male connector, 8 poles.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2903739

Packing unit 1

GTIN 4046356762038

Custom tariff number 85369010

Dimensions

Width 38 mm

Height 90 mm

Depth 60 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 55 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 24 V AC/DC

Max. perm. current (per branch) 2 A
Number of positions 8
Mounting position any
Assembly instructions In rows with zero spacing
Degree of protection IP00
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Spring-cage connection
Stripping length 7 mm
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 1.5 mm²
Conductor cross section AWG 24 ... 14
Number of positions 10
Connection data for connection 2
Connection name Controller level
Connection method M12-SAC plugs
Number of positions 8
Note Plug, 8-position, A-coded
Standards and Regulations
Connection in acc. with standard CUL
Designation Air clearances and creepage distances
Standards/regulations DIN EN 50178: 1998-04
Rated insulation voltage 50 V
Rated surge voltage 0.5 kV (1.2/50 us)
Insulation Functional insulation
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-M12/M/8P/2A/SC043 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.