


INDUSTRIAL COMPONENT DATA

FLKMS 40 2281584 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKMS 40



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKMS 40
Catalog number	2281584
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-5AB483F278
Generated	2026-08-04

Product Overview

Interface module

VARIOFACE module, with screw connection and plug-in connector for flat cable, for mounting on NS 32 or NS 35/7.5, with male connector, as well as short and long locking triggers for female connectors, number of poles 40

VARIOFACE module, with screw connection and flat-ribbon cable connector, for mounting on NS 32 or NS 35/7.5, with pin strip and short and long locking latches for socket strips, 40-pos.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2281584

Packing unit 5 pc

Note Made to Order (non-returnable)

Catalog page Page 243 (IF-2007)

GTIN 4017918054830

Weight per Piece (excluding packing) 169.090 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 79 mm

Height 77 mm

Depth 72 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage < 50 V AC

60 V DC

Max. perm. current (per branch) 1 A

Number of positions 40

Mounting position any

Degree of protection IP20

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Standards and Regulations

Standards/regulations IEC 60664

DIN EN 50178

Rated insulation voltage 63 V

Rated surge voltage 0.6 kV

Insulation Functional insulation

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss

7.027141152eCl@ss 8.027141152eCl@ss 9.027141152

ETIM 4.0EC002780ETIM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKMS 40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.