


INDUSTRIAL COMPONENT DATA

FLKMS-D25 SUB/B (1-25) 2294351 PHOENIX CONTACT

Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKMS-D25 SUB/B (1-25)



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKMS-D25 SUB/B (1-25)
Catalog number	2294351
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-BFCFE59786
Generated	2026-08-04

Product Overview

Interface module

VARIOFACE module, with screw connection and subminiature female connector D, for mounting on NS 35/7.5 or NS 32, number of poles 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2294351

Packing unit 5 pc

Catalog page Page 249 (IF-2007)

GTIN 4017918132750

Weight per Piece (excluding packing) 164.000 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 67.5 mm

Height 77 mm

Depth 72 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 25 V AC

60 V DC

Max. perm. current (per branch) 2.5 A

Number of positions 25

Status display No

Mounting position any

Degree of protection IP20

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Standards and Regulations

Standards/regulations IEC 60664

DIN EN 50178

Rated insulation voltage 125 V

Rated surge voltage 1.2 kV

Insulation Functional insulation

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss
7.027141152eCl@ss 8.027141152eCl@ss 9.027141152

ETIM 4.0EC002780ETIM 5.0EC002780ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKMS-D25 SUB/B (1-25) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.