

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FS-4CON-L180 VA 1404974 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FS-4CON-L180 VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FS-4CON-L180 VA
Catalog number	1404974
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-6FECA73B63
Generated	2026-08-04

Product Overview

Flush-type connector

Conect. plug. to be apar. wall poster., 4-pole, Connecting female, straight, M12, coding: A, Rear mounting, Pg9, Wave soldering, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) Item code: 1238708

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1404974

Packing unit 20 pc

Minimum order quantity 20 pc

Note Made to Order (non-returnable)

Catalog page Page 270 (C-2-2013)

GTIN 4046356740753

Weight per Piece (excluding packing) 15.200 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length of the solder pin 6 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 2.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Overvoltage category II

Degree of pollution 3

Test voltage 2.5 kV

Connection method Solder pins

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Rear mounting Pg9 With flat nut

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Stainless steel

Sealing material FKM

Cable

Standards/specifications M12 connector IEC 61076-2-101

Ambie...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FS-4CON-L180 VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.