

INDUSTRIAL COMPONENT DATA

SACC-SQ-M12MS-5CON-25F/0,5 1440973 PHOENIX CONTACT Sensor/Actuator flush-type plug, 5-pos., M12, A-coded, fr..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-SQ-M12MS-5CON-25F/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-SQ-M12MS-5CON-25F/0,5
Catalog number	1440973
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-E26E03EB94
Generated	2026-07-31

Product Overview

Sensor/Actuator flush-type plug, 5-pos., M12, A-coded, front/square flange mounting, with 0.5 m TPE litz wire, 5 x 0.34 mm² Conect. plug. to be apar. front wall, 5-pole, Male connector, straight, M12, coding: A, free cable end, Front mounting, Square flange, Single stranded wires, cable length: 0.5 m, 0.34 mm², TPE braided wire, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239716

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Dimensions

Length of cable 0.5 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 60 V

Rated surge voltage 1.5 kV
Number of positions 5
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Pollution degree 3
Test voltage 1.5 kV
Connection method Individual wires
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type Front mounting Square flange
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA 66
Material of grip body Zinc die-cast, nickel-plated
Material, knurls Zinc die-cast, nickel-plated
Sealing material FKM
Cable
Cable type TPE litz wire
Conductor cross section 0.34 mm^2
AWG signal line 22
Conductor structure signal line $7 \times 0.25 \text{ mm}$
Core diameter including insulation $1.2 \text{ mm} \pm 0.07 \text{ mm}$
Thickness, insulation 0.21 mm (Core insulation)
Wire colors Brown, white, blue, black, gray
Mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-SQ-M12MS-5CON-25F/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.