

INDUSTRIAL COMPONENT DATA

FBS 6-6 1008238 PHOENIX CONTACT Plug-in bridge

Brand: PHOENIX CONTACT | Manufacturer Part Number: FBS 6-6



Manufacturer	PHOENIX CONTACT
MPN / Reference	FBS 6-6
Catalog number	1008238
Category	Cross-connector for terminal block
Minimum order	10 Pcs
Document ID	EO-A5B457149D
Generated	2026-08-05

Product Overview

Plug-in bridge

Plug-in bridge, Variant with single or double-sided cutting edge. Be aware of the potential effects on accidental contact protection and leakage lines and air isolation distances. In applications in explosion-protected areas, the stress is reduced to that indicated in the EX certificate for cut bridges., one side not completely insulated, pitch: 6.2 mm, color: red

Plug-in bridge, One side not fully isolated, pitch: 6.2 mm, number of positions: 6, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataNotesNote on application Version with single- or double-sided cutting edge. Keep in mind the possible impact on touch protection as well as the air clearances and creepage distances. For applications in explosion-proof areas, the voltage reduces to the voltage specified in the Ex certificate for bridges that are cut to length.

Product propertiesProduct type Jumper

Number of positions 6

Pitch 6.2 mm

Data management status

Article revision 01

Electrical propertiesMaximum load current 32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Connection dataMaximum load current 32 A (The current values for the jumpers can deviate when used in different modular

terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

DimensionsWidth 35.5 mm

Height 23 mm

Depth 23 mm

Pitch 6.2 mm

Material specificationsColor red (RAL 3001)

Material Copper

Flammability rating according to UL 94 V0

Insulating material PA

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)

Ambient temperature (assembly) -5 °C ... 70....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBS 6-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.