


INDUSTRIAL COMPONENT DATA

FMC 1,5/ 5-ST-3,5 BK BD:6-10 1982392 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FMC 1,5/ 5-ST-3,5 BK BD:6-10



Manufacturer	PHOENIX CONTACT
MPN / Reference	FMC 1,5/ 5-ST-3,5 BK BD:6-10
Catalog number	1982392
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-23DF28BA34
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: FMC 1.5/.. -ST, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross-section: 1.5 mm², colour: black, rated current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Sn, contact connection type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, product series: FMC 1.5/.. -ST, pitch: 3.5 mm, connection type: Push-in spring connection, conductor/board connection direction: 0 °, plug system: COMBICON FMC 1.5 - MCDN 1.5, locking: none, fixing type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1982392

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918955137

Weight per Piece (excluding packing) 2.700 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 22.9 mm

Width [w] 18.25 mm

Height [h] 7.75 mm

Pitch 3.5 mm

Dimension a 14 mm

General

Range of articles FMC 1,5/...-ST

Number of positions 5

Connection method Push-in spring connection

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Minimum AWG according to UL/CUL 24

Maximum AWG according to UL/CUL 16

Specifications for ferrules

Recommended crimping pliers 1212034 CRIMPFOX 6

Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 5 mm ... 7 mm

Cross section: 0.34 mm²; Length: 7 mm

Cross section: 0.5 mm²; Length: 8 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FMC 1,5/ 5-ST-3,5 BK BD:6-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.