

INDUSTRIAL COMPONENT DATA

FOC-FDX20-PP-LCD6-OSA-PT9 1083665 PHOENIX CONTACT DIN rail splice box, fully mounted ready to splice, for 6x..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FOC-FDX20-PP-LCD6-OSA-PT9



Manufacturer	PHOENIX CONTACT
MPN / Reference	FOC-FDX20-PP-LCD6-OSA-PT9
Catalog number	1083665
Category	Patch panel fibre optic
Minimum order	1 Pcs
Document ID	EO-DDC48608B1
Generated	2026-08-04

Product Overview

DIN rail splice box, fully mounted ready to splice, for 6x LC duplex (OS2)

Splice box, construction: Rail mounting module, protection index: IP20, material: Metal, connection type: Splice, cable output: up and down, housing size: 1, color: gray, Ethernet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1083665

Packing unit 1 pc

Catalog page Page 381 (C-2-2019)

GTIN 4055626819518

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85367000

Country of origin DE (Germany)

Drawings

Ambient conditions

Material

Standards and Regulations

Dimensions

General

Connection data

Drawings

Dimensional drawing

DIN rail splice box 6x LC duplex OS2, fully mounted ready to splice

Back to topDimensions

External cable diameter 6 mm ... 12 mm

Back to topAmbient conditions

Ambient temperature (operation) -25 °C ... 70 °C

Ambient temperature (assembly) 0 °C ... 50 °C

Back to topGeneral

Tightening torque nut hand tight

Insertion/withdrawal cycles ≥ 500

Mounting type DIN rail mounting

Degree of protection IP20

Back to topMaterial

Color traffic grey A RAL 7042

Flammability rating according to UL 94 V0

Back to topConnection data

Connection method Cable gland M20

Cable type Single-mode fiberglass

Back to topStandards and Regulations

Flame resistance yes

Resistance to UV radiation yes

Halogen-free yes

Flammability rating according to UL 94 V0

Shock DIN EN 61300-2-9: 2015-09

Assignment plan International

Back to top

ETIM for 1083665 Data networking products (EC001130)

Feature Name

Feature Value

Fibre type (EF000080)

Other

Height (EF000040)

130 mm

Width (EF000008)

40 mm

Depth (EF000049)

115 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FOC-FDX20-PP-LCD6-OSA-PT9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.