

INDUSTRIAL COMPONENT DATA

FOC-FDX20-PP-LCD6-OSA-PT9 1083665 PHOENIX CONTACT DIN rail splice box, fully mounted ready to splice, for 6x..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FOC-FDX20-PP-LCD6-OSA-PT9



Manufacturer	PHOENIX CONTACT
MPN / Reference	FOC-FDX20-PP-LCD6-OSA-PT9
Catalog number	1083665
Category	Patch panel fibre optic
Minimum order	1 Pcs
Document ID	EO-DDC48608B1
Generated	2026-08-05

Product Overview

DIN rail splice box, fully mounted ready to splice, for 6x LC duplex (OS2)

Splice box, construction: Rail mounting module, protection index: IP20, material: Metal, connection type: Splice, cable output: up and down, housing size: 1, color: gray, Ethernet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1083665

Packing unit 1 pc

Catalog page Page 381 (C-2-2019)

GTIN 4055626819518

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85367000

Country of origin DE (Germany)

Drawings

Ambient conditions

Material

Standards and Regulations

Dimensions

[General](#)[Connection data](#)[Drawings](#)[Dimensional drawing](#)

DIN rail splice box 6x LC duplex OS2, fully mounted ready to splice

[Back to top](#)[Dimensions](#)

External cable diameter 6 mm ... 12 mm

[Back to top](#)[Ambient conditions](#)

Ambient temperature (operation) -25 °C ... 70 °C

Ambient temperature (assembly) 0 °C ... 50 °C

[Back to top](#)[General](#)

Tightening torque nut hand tight

Insertion/withdrawal cycles ≥ 500

Mounting type DIN rail mounting

Degree of protection IP20

[Back to top](#)[Material](#)

Color traffic grey A RAL 7042

Flammability rating according to UL 94 V0

[Back to top](#)[Connection data](#)

Connection method Cable gland M20

Cable type Single-mode fiberglass

[Back to top](#)[Standards and Regulations](#)

Flame resistance yes

Resistance to UV radiation yes

Halogen-free yes

Flammability rating according to UL 94 V0

Shock DIN EN 61300-2-9: 2015-09

Assignment plan International

[Back to top](#)

ETIM for 1083665 Data networking products (EC001130)

Feature Name

Feature Value

Fibre type (EF000080)

Other

Height (EF000040)

130 mm

Width (EF000008)

40 mm

Depth (EF000049)

115 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FOC-FDX20-PP-LCD6-OSA-PT9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.