

INDUSTRIAL COMPONENT DATA

FOC-FDX20-PP-SCD6-MM 1019686 PHOENIX CONTACT Splice box

Brand: PHOENIX CONTACT | Manufacturer Part Number: FOC-FDX20-PP-SCD6-MM



Manufacturer	PHOENIX CONTACT
MPN / Reference	FOC-FDX20-PP-SCD6-MM
Catalog number	1019686
Category	Patch panel fibre optic
Minimum order	1 Pcs
Document ID	EO-C8D18200DE
Generated	2026-08-03

Product Overview

Splice box

Distributor, construction: Module for rail mounting, protection index: IP20, material: Steel sheet, connection type: M20 cable glands, cable output: up and down, color: traffic gray A RAL 7042

Distributor, design: Rail-mountable module, degree of protection: IP20, material: Metal, connection method: Splicing, cable outlet: above and below, housing size: 1, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Technical dataNotesOrder information: Wire pigtails must be ordered separately

Product propertiesProduct type Network distributor box

Housing type DIN rail adapter

Series FDX 20 series

Type Rail-mountable module

Connection profile SC-Duplex

No. of cable outlets 2

Number of module slots 6

Number of slots 12

Type of the screw connection M20 x 1.5

Protective cover yes

Cable outlet above and below
Data management status
Article revision 10
Electrical propertiesTransmission medium FO
Connection dataConnection technology
Connection method Splicing
DimensionsWidth 40 mm
Height 130 mm
Depth 115 mm
Housing
Housing width 40 mm
Mechanical characteristics
Ferrule diameter 2.50 mm
Material specificationsColor gray
Flammability rating according to UL 94 V0
Ferrule material Zirconia ceramics
Housing material Metal
Housing surface material Powder-coated, gray
Cable/lineCable type Fiberglass
External cable diameter 6 mm ... 12 mm
External cable diameter 6 mm ... 12 mm
Wire diameter incl. insulation 900 µm
Resistance to oil no
Flame resistance yes
FO cable
Fiber GOF
Fiber type Multi-mode fiberglass
Transmission medium FO
Mechanical propertiesMechanical data
Type of the screw connection M20 x 1.5
Insertion/withdrawal cycles >= 500
Environmental and real-life conditionsAmbient conditions
Degree of protection IP20 (according to IEC 60529)
IP20
Ambient temperature (operation) -40 °C ... 85 °C (Category OPhd+)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Ambient temperature (assembly) 0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FOC-FDX20-PP-SCD6-MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.