

INDUSTRIAL COMPONENT DATA

FP 0,8/ 12-FV-SH 10,85 1154031 PHOENIX CONTACT Shielded SMD plug pin, rated current: 1.7 A, Test voltage: 50..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FP 0,8/ 12-FV-SH 10,85



Manufacturer	PHOENIX CONTACT
MPN / Reference	FP 0,8/ 12-FV-SH 10,85
Catalog number	1154031
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-490DBD35C3
Generated	2026-08-05

Product Overview

Shielded SMD plug pin, rated current: 1.7 A, Test voltage: 500 V AC, number of poles: 12, pitch: 0.8 mm, color: black, contact surface: Au, contact connection type: Female, mounting: SMD soldering

Shielded SMD plug pin, rated current: 1.7 A, test voltage: 500 VAC, number of poles: 12, pitch: 0.8 mm, color: black, surface contacts: Gold, contact type: Female, mounting: SMD solder

Shielded SMD female connector, nominal current: 1.7 A, Test voltage: 500 V AC, number of positions: 12, pitch: 0.8 mm, color: black, contact surface: Gold, contact connection type: Socket, mounting: SMD soldering

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type Shielded SMD female connector

Product family FP 0,8/...-FV-SH 10,85

Number of positions 12

Pitch 0.8 mm

Number of rows 2

Number of potentials 12

Pin layout Linear pad geometry

Electrical characteristic shielded

Electrical propertiesNominal current IN 1.7 A IEC 60512-5-2:2002-02 (at 20°C 80-pos.)

Degree of pollution 3

Contact resistance 25 m?

Test voltage 500 V AC IEC 60512-4-1:2003

Electrical characteristic shielded

MountingMounting type SMD soldering

Pin layout Linear pad geometry

Processing notes

Process Reflow soldering

Moisture Sensitive Level MSL 1

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics Selective coating

Metal surface contact area (top layer) Gold (Au)

Metal surface contact area (middle layer) Nickel (Ni)

Metal surface soldering area (top layer) Tin (Sn)

Metal surface soldering area (middle layer) Nickel (Ni)

Material data - housing

Color (Housing) black (9005)

Insulating material LCP

Insulating material group IIIb

CTI according to IEC 60112 150

Flammability rating according to UL 94 V0

Connection dataCross section AWG (converted acc. to IEC)

NotesNotes on operation The permissible voltage during operation depends on the application, taking into consideration the air clearances and creepage distances within the scope of insulation requirements in accordance with IEC 60664-1.

Details f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FP 0,8/ 12-FV-SH 10,85 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.