

INDUSTRIAL COMPONENT DATA

FP 0,8/ 12-MH-SH 1043791 PHOENIX CONTACT Shielded SMD blade strip, Rated current with 20 °C: 1.7 A, Test vol..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FP 0,8/ 12-MH-SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	FP 0,8/ 12-MH-SH
Catalog number	1043791
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-3319FA66EB
Generated	2026-08-05

Product Overview

FP 0,8/ 12-MH-SH 1043791 PHOENIX CONTACT Shielded SMD blade strip, Rated current with 20 °C: 1.7 A, Test vol..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Type of accessory/spare part	Charger
Mains voltage	100 V - 240 V AC
Suitable for	CF-CRIMPHANDY
Output voltage	12 V DC
Charging current	2 A

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Shielded SMD blade strip, Rated current with 20 °C: 1.7 A, Test voltage: 500 V AC, number of poles: 12, pitch: 0.8 mm, colour: black, surface contacts: Gold, contact type: Male

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FP 0,8/ 12-MH-SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.