

**INDUSTRIAL COMPONENT DATA**

# FP 0,8/ 80-MV-SH 1,15 1043790 PHOENIX CONTACT Strip blades SMD apantallada, rated Current at 20 °C: 1.7 A, t..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FP 0,8/ 80-MV-SH 1,15



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | FP 0,8/ 80-MV-SH 1,15           |
| Catalog number  | 1043790                         |
| Category        | Printed circuit board connector |
| Minimum order   | 500 Pcs                         |
| Document ID     | EO-CBCE91D8BD                   |
| Generated       | 2026-08-05                      |

## Product Overview

Strip blades SMD apantallada, rated Current at 20 °C: 1.7 A, test Voltage: 500 V AC, number of pole: 80, step: 0.8 mm, color: black, surface contacts: Gold, assembly: Soldering SMD

Shielded SMD blade strip, rated current: 1.7 A, Test voltage: 500 VAC, number of poles: 80, pitch: 0.8 mm, color: black, contact surface: Gold, contact type: Male, mounting: SMD welding

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

ETIM for 1043790 Connectors (EC002637)

Feature Name

Feature Value

Contact type (EF001587)

Pin

Number of poles (EF001391)

80

Number of plug-in contact rows (EF006935)

2

Modular spacing contacts (EF007326)

0.8 mm

Modular spacing connections (EF006827)

0.8 mm

Rated current  $I_n$  (EF008250)

1.7 A

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Gold

Type of electric connection (EF003961)

Other

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Black

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-55 °C

Type of banding (EF007011)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FP 0,8/ 80-MV-SH 1,15 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.