

INDUSTRIAL COMPONENT DATA

FP 1,27/ 20-MV 3,25 1714927 PHOENIX CONTACT Strip blades SMD, rated Current to 20A °C: 1.4 A, test Voltage: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FP 1,27/ 20-MV 3,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	FP 1,27/ 20-MV 3,25
Catalog number	1714927
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-149B2BB076
Generated	2026-08-06

Product Overview

FP 1,27/ 20-MV 3,25 1714927 PHOENIX CONTACT Strip blades SMD, rated Current to 20A °C: 1.4 A, test Voltage: ..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Type of accessory/spare part	Charger
Mains voltage	100 V - 240 V AC
Suitable for	CF-CRIMPHANDY
Output voltage	12 V DC
Charging current	2 A

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Strip blades SMD, rated Current to 20A °C: 1.4 A, test Voltage: 500 V AC, number of poles: 20, pitch: 1.27 mm, color: black, surface contacts: Gold, assembly: Soldering SMD

SMD blade strip, rated current: 1.4 A, Test voltage: 500 V AC, number of poles: 20, pitch: 1.27 mm, color: black, contact surface: Gold, contact type: Male, mounting: SMD welding

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FP 1,27/ 20-MV 3,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.