

**INDUSTRIAL COMPONENT DATA**

# FP 1,27/ 68-MV 3,25 1714932 PHOENIX CONTACT Strip blades SMD, rated Current to 20A °C: 1.4 A, test Voltage: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FP 1,27/ 68-MV 3,25



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | FP 1,27/ 68-MV 3,25             |
| Catalog number  | 1714932                         |
| Category        | Printed circuit board connector |
| Minimum order   | 280 Pcs                         |
| Document ID     | EO-1E64D68795                   |
| Generated       | 2026-08-06                      |

## Product Overview

Strip blades SMD, rated Current to 20A °C: 1.4 A, test Voltage: 500 V AC, number of poles: 68, pitch: 1.27 mm, color: black, surface contacts: Gold, assembly: Soldering SMD

SMD blade strip, rated current: 1.4 A, Test voltage: 500 V AC, number of poles: 68, pitch: 1.27 mm, color: black, contact surface: Gold, contact type: Male, mounting: SMD welding

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FP 1,27/ 68-MV 3,25 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.