

INDUSTRIAL COMPONENT DATA

FR 1,27/ 26-FV 6,25 1374030 PHOENIX CONTACT SMD plug pin, rated current: 2.2 A, Test voltage: 840 V AC, numb..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FR 1,27/ 26-FV 6,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	FR 1,27/ 26-FV 6,25
Catalog number	1374030
Category	Printed circuit board connector
Minimum order	280 Pcs
Document ID	EO-957FD6D699
Generated	2026-08-05

Product Overview

SMD plug pin, rated current: 2.2 A, Test voltage: 840 V AC, number of poles: 26, pitch: 1.27 mm, color: black, contact surface: Au, contact connection type: Female, mounting: SMD welding

SMD plug plug, rated current: 2.2 A, test voltage: 840 VAC, number of poles: 26, pitch: 1.27 mm, color: black, surface contacts: gold, contact type: female, mounting: SMD solder

SMD Spring Strip, Rated Current: 2.2 A, Test Voltage: 840 V AC, Number of Poles: 26, Pitch: 1.27 mm, Color: Black, Contact Surface: Gold, Contact Type: Socket, Mounting: SMD Soldering

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataItem propertiesProduct Type SMD Spring Strip

Product family FR 1,27/.. -FV 6.25

Number of poles 26

Grid dimension 1.27 mm

Number of rows 2

Pin layout Linear pad geometry

Electrical propertiesNominal current IN 2.2 A IEC 60512-5-2:2002-02 (at 20 °C 100-pin)

Degree of contamination 3

Contact resistance 10 mΩ

Test voltage 840 V AC IEC 60512-4-1:2003

AssemblyMounting type SMD Soldering

Pin layout Linear pad geometry

Processing instructions

Process Reflow soldering

Moisture Sensitive Level MSL 1

Classification Temperature Tc 260 °C

Soldering cycles in reflow 3

Material specificationsMaterial information - Contact

Note WEEE/RoHS compliant, whisker-free according to IEC 60068-2-82/JEDEC JESD 201

Material Contact Cu alloy

Surface finish Selective coating

Metal Surface Contact Area (Top Layer) Gold (Au)

Metal Surface Contact Area (Interlayer) Nickel (Ni)

Metal Surface Soldering Area (Top Layer) Tin (Sn)

Metal Surface Soldering Area (Interlayer) Nickel (Ni)

Material specifications - Housing

Color (Housing) black (9005)

Insulating material LCP

Insulating material group IIIb

CTI according to IEC 60112 150

Flammability class according to UL 94 V0

Connection dataConductor cross-section AWG (converted to IEC)

RemarksNote on operation The permissible voltage in operation depends on the application, taking into account the clearance and creepage distances within the framework of the insulation requirements according to IEC 60664-1.

DimensionsDimensional drawing

Grid dimension 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FR 1,27/ 26-FV 6,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.