


INDUSTRIAL COMPONENT DATA

MDSTBW 2,5/ 6-G-5,08 (1357911) 1972506 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MDSTBW 2,5/ 6-G-5,08 (1357911)



Manufacturer	PHOENIX CONTACT
MPN / Reference	MDSTBW 2,5/ 6-G-5,08 (1357911)
Catalog number	1972506
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-D246AC7DF9
Generated	2026-08-06

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 10 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 2, number of poles: 6, number of connections: 6, family of articles: MDSTBW 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.8 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

PCB header, nominal cross-section: 2.5 mm², colour: green, nominal current: 10 A, reference voltage (III/2): 320 V, contact area: Sn, contact type: Male, number of potentials: 6, number of rows: 2, number of poles: 6, number of connections: 6, item range: MDSTBW 2.5/.. -G, pitch: 5.08 mm, mounting: Wave welding, spindle plane: Linear pinout, spindle length [P]: 3.8 mm, number of pins per potential: 1, Plug-in system: COMBICON MSTB 2.5, Orientation of the plug-in pattern: Standard, locking: without, fastening type: without, packaging type: packed in a carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1972506

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918939588

Weight per Piece (excluding packing) 8.280 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 22.1 mm

Width 33.03 mm

Pitch 5.08 mm

Dimension a 25.4 mm

Width [w] 33.03 mm

Height [h] 31.8 mm

Height 28 mm

Length of the solder pin 3.8 mm

Pin dimensions 1 x 1 mm

Length 22.1 mm

General

Range of articles MDSTBW 2,5/..-G

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 10 A

Color green

Number of positions 6

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1972506 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

6

Number of plug-in contact rows (EF006935)

2

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Rated current I_n (EF008250)

10 A

Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MDSTBW 2,5/ 6-G-5,08 (1357911) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.