

INDUSTRIAL COMPONENT DATA

FRONT 2,5-H/SA 5-EX/11 BD-11SO 1258201 PHOENIX CONTACT Printed circuit board terminal, rated current: 21 A, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT 2,5-H/SA 5-EX/11 BD-11SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT 2,5-H/SA 5-EX/11 BD-11SO
Catalog number	1258201
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-30235AE48F
Generated	2026-08-04

Product Overview

Printed circuit board terminal, rated current: 21 A, nominal cross-section: 2.5 mm², number of rows: 1, number of poles per row: 11, article family: FRONT 2.5-H-EX, pitch: 5 mm, connection type: Front screw connection, mounting: Wave soldering, driver/printed circuit board connection direction: 0 °, color: green, Pin length [P]: 3.5 mm, number of solder pins per potential: 2

Printed circuit board terminal, rated current: 21 A, nominal section: 2.5 mm², Number of rows: 1, Number of poles per row: 11, item family: FRONT 2,5-H-EX, pitch: 5 mm, connection type: Front screw connection, mounting: Wave welding, connection direction conductor/printed circuit board: 0 °, colour: green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT 2,5-H/SA 5-EX/11 BD-11SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.