


INDUSTRIAL COMPONENT DATA

MCV 1,5/ 4-G-3,5 P26 THR CP2 1806516 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 4-G-3,5 P26 THR CP2



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 4-G-3,5 P26 THR CP2
Catalog number	1806516
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-2726480EC5
Generated	2026-08-06

Product Overview

Feed-through header

Base case printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MCV 1.5/.. -G-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1806516

Packing unit 1

GTIN 4046356692601

Custom tariff number 85366930

Dimensions

Length [l] 6.9 mm

Width 15.4 mm

Pitch 3.5 mm

Dimension a 10.5 mm

Width [w] 15.4 mm

Height [h] 11.8 mm

Height 9.2 mm

Length of the solder pin 2.6 mm

Pin dimensions 0.8 x 0.8 mm

Length 6.9 mm

General

Range of articles MCV 1,5/..-G-THR

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Color black

Number of positions 4

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1806516 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

4

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Rated current In (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 4-G-3,5 P26 THR CP2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.