

INDUSTRIAL COMPONENT DATA

FRONT 2,5-V/SA10/ 4 VPE50 1707819 PHOENIX CONTACT

Printed circuit board terminal, rated current: 24 A, rated..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT 2,5-V/SA10/ 4 VPE50



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT 2,5-V/SA10/ 4 VPE50
Catalog number	1707819
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-8A5F71ED0A
Generated	2026-08-04

Product Overview

Printed circuit board terminal, rated current: 24 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of potentials: 4, number of rows: 1, number of poles per row: 4, article family: FRONT 2.5-V/SA10, pitch: 5 mm, connection type: Front screw connection, mounting: Wave soldering, driver/printed circuit board connection direction: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of solder pins per potential: 2

Printed circuit board terminal, rated current: 24 A, sizing voltage (III/2): 400 V, nominal section: 2.5 mm², Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, item family: FRONT 2,5-V/SA10, pitch: 5 mm, connection type: Front screw connection, mounting: Wave welding, Connection direction conductor/printed circuit board: 90°, color: green, Pin arrangement: Double linear pin arrangement, Pin length [P]: 3.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

ETIM for 1707819 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

24.5 mm

Number of electrical connections (EF008252)

4

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current I_n (EF008250)

24 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section multi-wired (EF007343)

0.2 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.2 mm

Length pin (EF006825)

5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT 2,5-V/SA10/ 4 VPE50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.