

INDUSTRIAL COMPONENT DATA

ISPC 5/ 2-STGCL-7,62 BD D-,D+ 1710916 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ISPC 5/ 2-STGCL-7,62 BD D-,D+



Manufacturer	PHOENIX CONTACT
MPN / Reference	ISPC 5/ 2-STGCL-7,62 BD D-,D+
Catalog number	1710916
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-5E58976CA9
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: ISPC 5/.. -STGCL, pitch: 7.62 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, clamping hook: - without clamping hook, plug-in system: COMBICON PC 5, locking: Clip lock, fixing type: Click & Lock locking window, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1710916

Packing unit 1

GTIN 4055626193779

Custom tariff number 85366990

Dimensions

Length [l] 40.5 mm

Width [w] 18.04 mm

Height [h] 19.8 mm

Pitch 7.62 mm

Dimension a 7.62 mm

General

Range of articles ISPC 5/...-STGCL

Number of positions 2

Connection method Push-in spring connection

Insulating material group I

Rated voltage (III/2) 1000 V

Nominal current IN 41 A

Nominal cross section 6 mm²

Flammability rating according to UL 94 V0

Specifications for ferrules

Recommended crimping pliers 1212034 CRIMPFOX 6

Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.5 mm²; Length: 10 mm ... 15 mm

Cross section: 0.75 mm²; Length: 10 mm ... 15 mm

Cross section: 1 mm²; Length: 10 mm ... 15 mm

Cross section: 1.5 mm²; Length: 12 mm ... 15 mm

Cross section: 2.5 mm²; Length: 12 mm ... 15 mm

Cross section: 4 mm²; Length: 12 mm ... 15 mm

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638

UNSPSC 13.239121409

ETIM for 1710916 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Other

Number of poles (EF001391)

2

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ISPC 5/ 2-STGCL-7,62 BD D-,D+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.