


INDUSTRIAL COMPONENT DATA

FRONT 4-H-7,62-4 1703212 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT 4-H-7,62-4



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT 4-H-7,62-4
Catalog number	1703212
Category	Printed circuit board terminal
Minimum order	10 Pcs
Document ID	EO-877C7E4C73
Generated	2026-08-03

Product Overview

PCB terminal block

Printed circuit board terminal block, nominal current: 32 A, nominal voltage (III/2): 630 V, nominal cross-section: 4 mm², number of potentials: 4, number of rows: 1, number of poles per row: 4, article family: FRONT 4-H, pitch: 7.62 mm, connection type: Front screw connection, mounting: Wave soldering, driver/printed circuit board connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of solder pins per potential: 2, packaging type: boxed

Printed circuit board terminal, nominal current: 32 A, rated voltage (III/2): 630 V, nominal cross section: 4 mm², number of potentials: 4, number of rows: 1, number of positions per row: 4, product range: FRONT 4-H, pitch: 7.62 mm, connection method: Front screw connection, mounting: Wave soldering, conductor/PCB connection direction: 0°, color: green, Pin layout: Linear pinning, Solder pin [P]: 5 mm, number of solder pins per potential: 2, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family FRONT 4-H

Product line COMBICON Terminals L

Type PC terminal block can be aligned

Number of positions 4

Pitch 7.62 mm

Number of connections 4

Number of rows 1

Number of potentials 4

Pin layout Linear pinning

Solder pins per potential 2

Data management status

Article revision 05

Electrical propertiesNominal current IN 32 A

Nominal voltage UN 630 V

Rated voltage (III/3) 500 V

Rated surge voltage (III/3) 6 kV

Rated voltage (III/2) 630 V

Rated surge voltage (III/2) 6 kV

Rated voltage (II/2) 1000 V

Rated surge voltage (II/2) 6 kV

Connection dataConnection technology

Type PC terminal block can be aligned

Nominal cross section 4 mm²

Conductor connection

Connection method Front screw connection

Conductor cross section rigid 0.5 mm² ... 6 mm²

Conductor cross section flexible 0.5 mm² ... 6 mm²

Conductor cross section AWG 20 ... 10

Conductor cross section flexible, with ferrule without plastic sleeve 0.5 mm² ... 4 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.5 mm² ... 4 mm²

2 conductors with same cross section, solid 0.5 mm² ... 1.5 mm²

2 conductors with same cross section, flexible 0.5 mm² ... 1.5 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²

Stripping length 14 mm

Tightening torque 0.5 Nm ... 0.6 Nm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT 4-H-7,62-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.