

INDUSTRIAL COMPONENT DATA

**FRONT-GMSTB 2,5/ 3-ST-7,62 BK 1995004 PHOENIX
CONTACT Printed-circuit board connector**

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT-GMSTB 2,5/ 3-ST-7,62 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT-GMSTB 2,5/ 3-ST-7,62 BK
Catalog number	1995004
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-72A3B43079
Generated	2026-08-03

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: FRONT-GMSTB 2.5/.. -ST, pitch: 7.62 mm, connection type: Front screw connection, screw clamping shape: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1995004

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918991234

Weight per Piece (excluding packing) 9.710 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 27.3 mm

Width [w] 20.86 mm

Height [h] 15 mm

Pitch 7.62 mm

Dimension a 15.24 mm

General

Range of articles FRONT-GMSTB 2,5/...-ST

Number of positions 3

Connection method Front screw connection

Rated voltage (III/3) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 2.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1.5 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT-GMSTB 2,5/ 3-ST-7,62 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.