

INDUSTRIAL COMPONENT DATA

FRONT-MC 1,5/11-ST-3,81 BK 1898732 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT-MC 1,5/11-ST-3,81 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT-MC 1,5/11-ST-3,81 BK
Catalog number	1898732
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-DBCF42B835
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, family of articles: FRONT-MC 1.5/.. -ST, pitch: 3.81 mm, connection type: Front screw connection, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1898732

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918422295

Weight per Piece (excluding packing) 14.170 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 21.7 mm

Width [w] 42.7 mm

Height [h] 12.3 mm

Pitch 3.81 mm

Dimension a 38.1 mm

General

Range of articles FRONT-MC 1,5/..-ST

Number of positions 11

Connection method Front screw connection

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Maximum load current 8 A (with 1.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 9 mm

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT-MC 1,5/11-ST-3,81 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.