

INDUSTRIAL COMPONENT DATA

FRONT-MC 1,5/ 8-STF-3,81BU8-1Q 1733783 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT-MC 1,5/ 8-STF-3,81BU8-1Q



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT-MC 1,5/ 8-STF-3,81BU8-1Q
Catalog number	1733783
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-C3F7C73E8B
Generated	2026-08-03

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², colour: blue, rated current: 8 A, dimensioning voltage (III/2): 160 V, surface contacts: Tin, contact type: Connecting female, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, number of connections: 8, article family: FRONT-MC 1.5/.. -STF, pitch: 3.81 mm, connection type: Front screw connection, conductor/printed circuit board connection direction: 0°, Stecksyst:MINI COMBICON, Lock: Screw lock, packing type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1733783

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356165709

Weight per Piece (excluding packing) 10.850 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 21.7 mm

Width [w] 40.87 mm

Height [h] 12.3 mm

Pitch 3.81 mm

Dimension a 26.67 mm

General

Range of articles FRONT-MC 1,5/...-STF

Number of positions 8

Connection method Front screw connection

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 28

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.14 mm²

2 conductors with same cross section, solid max. 0.5 mm²

2 conductors with same cross section, stranded min. 0.14 mm²

2 conductors with same cross section, stranded max. 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT-MC 1,5/ 8-STF-3,81BU8-1Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.