

INDUSTRIAL COMPONENT DATA

FRONT-MSTB 2,5/24-ST-5,08 1777507 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT-MSTB 2,5/24-ST-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT-MSTB 2,5/24-ST-5,08
Catalog number	1777507
Category	Cable connector
Minimum order	2000 Pcs
Document ID	EO-F88E871DCA
Generated	2026-08-04

Product Overview

Plug

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 24, number of rows: 1, number of poles: 24, number of connections: 24, family of articles: FRONT-MSTB 2.5/.. -ST, pitch: 5.08 mm, connection type: Front screw connection, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1777507

Packing unit 50 pc

Catalog page Page 132 (CC-2005)

GTIN 4017918039653

Weight per Piece (excluding packing) 71.270 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 27.2 mm

Width [w] 121.92 mm

Height [h] 14.9 mm

Pitch 5.08 mm

Dimension a 116.84 mm

General

Range of articles FRONT-MSTB 2,5/..-ST

Number of positions 24

Connection method Front screw connection

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 10 mm

Screw thread M2,5

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.34 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT-MSTB 2,5/24-ST-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.