

INDUSTRIAL COMPONENT DATA

FRONT-MSTB 2,5/ 3-ST-5,0835BDM 1094609 PHOENIX CONTACT Connector for printed circuit board, nominal current:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT-MSTB 2,5/ 3-ST-5,0835BDM



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT-MSTB 2,5/ 3-ST-5,0835BDM
Catalog number	1094609
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-F05751FE74
Generated	2026-08-04

Product Overview

Connector for printed circuit board, nominal current: 12 A, number of poles: 3, pitch: 5,08 mm, type of connection:

Connection by screw-on front, color: grey, surface contacts: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: luminous gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of rows: 1, number of poles: 3, family of articles:

FRONT-MSTB 2,5/..-ST, pitch: 5.08 mm, connection type: Front screw connection, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2,5, locking: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 2.5 mm², color: light gray, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Socket, number of rows: 1, number of positions: 3, product range: FRONT-MSTB 2,5/..-ST, pitch: 5.08 mm, connection method: Front screw connection, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family FRONT-MSTB 2,5/..-ST

Product line COMBICON Connectors M

Number of positions 3

Pitch 5.08 mm

Number of rows 1

Data management status

Article revision 00

Electrical propertiesNominal current IN 12 A

Nominal voltage UN 320 V

Contact resistance 1.5 mΩ

Rated voltage (III/3) 250 V

Rated surge voltage (III/3) 4 kV

Rated voltage (III/2) 320 V

Rated surge voltage (III/2) 4 kV

Rated voltage (II/2) 630 V

Rated surge voltage (II/2) 4 kV

Connection dataConnection technology

Type Standard

Connector system COMBICON MSTB 2,5

Nominal cross section 2.5 mm²

Contact connection type Socket

Interlock

Locking type without

Mounting flange without

Conductor connection

Connection method Front screw connection

Conductor/PCB connection direction 0 °

Conductor cross section rigid 0.34 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.2 mm² ... 1 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1.5 mm²

Cylindrical gauge a x b / di...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT-MSTB 2,5/ 3-ST-5,0835BDM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.