

**INDUSTRIAL COMPONENT DATA**

# SI-FP-R1A-R2A-2U1A 1404503 PHOENIX CONTACT Front plate

Brand: PHOENIX CONTACT | Manufacturer Part Number: SI-FP-R1A-R2A-2U1A



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | SI-FP-R1A-R2A-2U1A               |
| Catalog number  | 1404503                          |
| Category        | Front plate (switchgear cabinet) |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-FE899C1C75                    |
| Generated       | 2026-08-03                       |

## Product Overview

Front plate

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                            |
|--------------|------------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |
|--------------|------------------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1404503

Packing unit 1 pc

Catalog page Page 717 (C-2-2017)

GTIN 4046356698450

Weight per Piece (excluding packing) 94.200 g

Custom tariff number 85366990

Country of origin CZ (Czech Republic)

Mechanical characteristics

Shielded yes

Degree of protection IP20

Contact insert design with 1x RJ45 Socket/socket, snap-in slot locking

with 2x USB A 3.0 Socket/socket, snap-in slot locking

with 1x RJ12 Socket/socket, snap-in slot locking

Type of note Assembly instruction:

Note

Ambient conditions

Ambient temperature (operation) -10 °C ... 60 °C

Material data

Material PBT (Front plate)

Depth 60 mm

Height 87.5 mm

Electrical characteristics

Rated voltage (III/3) max. 42.4 V DC ()

Rated current 1.5 A ()

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027189239eCl@ss 5.127189200eCl@ss 6.027189200eCl@ss  
7.027189217eCl@ss 8.027189217eCl@ss 9.027189217

ETIM 3.0EC000007ETIM 4.0EC001855ETIM 5.0EC000456ETIM 6.0EC000456

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC  
13.239121302

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SI-FP-R1A-R2A-2U1A with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.